BM GROUP	**Technical sheet**	**No.** 11FA06A **Issue** V01.1

Product family:	Cable-ties - Nylon cable-ties
Item code:	BH1125, BH2048, BH3076
Description:	NYLON CABLE-TIES · WITH MOUNTING HOLE

Image

Specifications

MATERIAL:	polyamide (PA 6.6)
COLOR:	natural
INSULATION SELF-EXTINGUISHING:	UL 94 V2
OPERATING TEMPERATURE:	from -40 °C to +85 °C
MINIMUM INSTALLATION TEMPERATURE:	-10 °C
CHEMICAL RESISTANCE:	good resistance to bases, oils, grease, chloride solvents. Limited resistance to acids. Not resistant to phenols.
ACCORDING TO STD.:	EN 62275:2015-02
CLASSIFICATION:	type 1 (EN), type 21 (UL)
ASSEMBLY:	open the package just before use

Code	Width (mm)	Length (mm)	Fixing hole Ø (mm)	Max bundle Ø (mm)	Min bundle Ø (mm)	Tensile minimum resistance (N)	
BH1125	2,5	110	3	19	3	80	100/3000
BH2048*	4,8	200	4,8	49,8	3	230	100/1000
BH3076*	7,6	305	6,1	78,7	8	550	100/1000

CE UL LISTED * file n° E 223175

HALOGEN FREE