BM GROUP	**Technical sheet**	**No.** 11FA09A **Issue** V01.0

Product family:	Cable-ties - Nylon cable-ties UV resistant
Item code:	N2412, N4912, N7412, N8912, N1012
Description:	UV-RESISTANT NYLON CABLE-TIES · FOR HEAVY LOADS

Image

Specifications

MATERIAL:	polyamide (PA 6.6) + carbon black
COLOR:	black
OPERATING TEMPERATURE:	from -40 °C to +85 °C
MINIMUM INSTALLATION TEMPERATURE:	-10 °C
CHEMICAL RESISTANCE:	good resistance to bases, oils, grease, chloride solvents. Limited resistance to acids. Not resistant to phenols.
ACCORDING TO STD.:	EN 62275:2015-02
CLASSIFICATION:	type 1 (EN), type 21 (UL)
ASSEMBLY:	open the package just before use

Code	Width (mm)	Length (mm)	Max bundle Ø (mm)	Min bundle Ø (mm)	Tensile minimum resistance (N)	
N2412	12,4	230	57	9	1200	
N4912	12,4	480	136,5	9	1200	
N7412	12,4	730	216,1	9	1200	100/100
N8912	12,4	880	263,9	9	1200	
N1012	12,4	1000	305	9	1200	

CE UL LISTED file n° E 223175

HALOGEN FREE

UV RESISTANT