



Specyfikacja techniczna

No.	11TB04F
Wersja	V01.4

Rodzina produktów:	Końcówki - Końcówki kablowe izolowane
Kod towaru:	001071, 001191, 001251, 001311, 002191, 002251, 002311, 003191, 003251, 003311, 003371, 003431, 00419, 00420, 00431, 00432, 00437, 00438, 00443, 00444, 00525, 00526, 00531, 00532, 00537, 00538, 00543, 00544, 00547, 00549, 00625, 00626, 00631, 00632, 00637, 00638, 00643, 00644, 00649, 006492, 00731, 00732, 00737, 00738, 00743, 00744, 00749, 00752, 00831, 00832, 00837, 00838, 00843, 00844, 00849, 00852, 00855, 00856, 00937, 00943, 00949, 00955, 00961, 05137, 05143, 05149, 05155, 05161, 05237, 05243, 05249, 05255, 05261, 05337, 05343, 05349, 05355, 05361, 05367, 05449, 05455, 05461, 05467, 05549, 05555, 05561, 05567
Opis:	KOŃCÓWKI KABLOWE DO PRZEWODÓW MIEDZIANYCH · IZOLOWANE NYLONEM · KOLOROWE

Obraz

Obrazy wymiary

Dane techniczne	
MATERIAŁ KOŃCÓWKI:	miedź cynowana
MATERIAŁ IZOLACJI:	poliamid (PA6.6)
POZIOM SAMOGAŚNIĘCIA IZOLACJI:	UL 94 V2
TEMPERATURA ROBOCZA:	130 °C maks.
KLASA PRZEWODNIKA:	Klasa 1 i 2 (przewód sztywny) oraz klasa 5 (przewód giętki) zgodnie z EN 60228

Kod		Kolor	Rozdział (mm²)	Rozdział (AWG/kcmil)	Do śruby Ø śruby (mm)	Do śruby Rozmiar szpilki	W1 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	D1 (mm)	D2 (mm)	D3 (mm)	S1 (mm)	
001071		Czerwony	1.5	(16)	3	#4	8	21,6	5	5	4	4,2	1,9	3,2	1	100/100
001191		Czerwony	1.5	(16)	4	#8	8	21,6	5	5	4	4,2	1,9	4,2	1	
001251		Czerwony	1.5	(16)	5	#10	8	21,6	5	5	4	4,2	1,9	5,2	1	
001311		Czerwony	1.5	(16)	6	#12	10	23,6	5	6	5	4,2	1,9	6,3	0,8	
002191		Niebieski	2.5	(14)	4	#8	8	23,7	7	5	4	4,8	2,4	4,2	1	100/1000
002251		Niebieski	2.5	(14)	5	#10	10	25,7	7	6	5	4,8	2,4	5,2	0,8	
002311		Niebieski	2.5	(14)	6	#12	10	25,7	7	6	5	4,8	2,4	6,3	0,8	
003191		Żółty	6	(10)	4	#8	10	29,8	9	6	5	6,6	3,5	4,2	1,4	
003251		Żółty	6	(10)	5	#10	10	29,8	9	6	5	6,6	3,5	5,2	1,4	100/100
003311		Żółty	6	(10)	6	#12	10	29,8	9	6	5	6,6	3,5	6,3	1,4	
003371		Żółty	6	(10)	8	5/16"	12	33,8	9	9	6	6,6	3,5	8,2	1,2	
003431		Żółty	6	(10)	10	3/8"	15	38,8	9	11	9	6,6	3,5	10,2	0,9	
00419		Czerwony	10	(8)	5	#10	10	37,3	9,5	6,3	5	16	5	5,2	100/100	
00420		Czerwony	10	(8)	5	#10	10	44,5	9,5	6,3	5	14,8	5	5,2		
00431		Czerwony	10	(8)	6	#12	11	38,8	9,5	6,5	5,5	8,2	5	6,3		
00432		Czerwony	10	(8)	6	#12	11	46	9,5	6,5	5,5	14,8	5	6,3		
00437		Czerwony	10	(8)	8	5/16"	13,6	42,3	9,5	8,8	6,2	16	5	8,5		
00438		Czerwony	10	(8)	8	5/16"	13,6	49,5	9,5	8,8	6,2	14,8	5	8,5		
00443		Czerwony	10	(8)	10	3/8"	17,2	44,8	9,5	9,6	9,5	16	5	10,5		
00444		Czerwony	10	(8)	10	3/8"	17,2	52	9,5	9,6	9,5	14,8	5	10,5		
00525		Niebieski	16	(6)	5	#10	11,5	43,3	11	8,7	6,3	9	6	5,3		
00526		Czerwony	16	(6)	5	#10	11,5	52,8	11	8,7	6,3	16	6	5,3		
00531		Niebieski	16	(6)	6	#12	11,5	43,8	11	8,5	6	9	6	6,5		
00532		Czerwony	16	(6)	6	#12	11,5	53,8	11	8,5	6	16	6	6,5		
00537		Niebieski	16	(6)	8	5/16"	15	48,8	12	9	8	9	6	8,5		
00538		Czerwony	16	(6)	8	5/16"	15	58,3	12	9	8	16	6	8,5	50/50	
00543		Niebieski	16	(6)	10	3/8"	17,5	51,3	12	10,5	10	9	6	10,5	100/100	
00544		Czerwony	16	(6)	10	3/8"	17,5	60,8	12	10,5	10	16	6	10,5		
00547		Czerwony	16	(6)	12	1/2"	17,5	61,3	12	10,5	10	16	6	13		
00549		Niebieski	16	(6)	12	1/2"	17,5	51,8	12	10,5	10	9	6	13		
00625		Żółty	25	(4)	5	#10	14	49,4	13,5	10	7	11,5	7	5,2	100/100	
00626		Czerwony	25	(4)	5	#10	14	58,4	13,5	10	7	16,8	7	5,2		
00631		Żółty	25	(4)	6	#12	14	49,4	13,5	10	7	11,5	7	6,3		
00632		Czerwony	25	(4)	6	#12	14	58,4	13,5	10	7	16,8	7	6,3		
00637		Żółty	25	(4)	8	5/16"	14	49,4	13,5	10	8	11,5	7	8,4	25/25	
00638		Czerwony	25	(4)	8	5/16"	14	58,4	13,5	10	8	16,8	7	8,4		
00643		Żółty	25	(4)	10	3/8"	17	53,4	14	10,5	9,5	11,5	7	10,5	100/100	
00644		Czerwony	25	(4)	10	3/8"	17	62,4	14	10,5	9,5	16,8	7	10,5		
00649		Żółty	25	(4)	12	1/2"	18,5	53,4	14	11	9,5	11,5	7	13		
006492		Czerwony	25	(4)	12	1/2"	18,5	62,4	14	11	9,5	16,8	7	13	25/25	
00731		Czerwony	35	(2)	6	#12	17	53	15	9,5	6	14	8,5	6,4	100/100	
00732		Czerwony	35	(2)	6	#12	17	61	15	9,5	6	18,7	8,5	6,4		
00737		Czerwony	35	(2)	8	5/16"	17	57,5	15	10,5	10	14	8,5	8,5		
00738		Czerwony	35	(2)	8	5/16"	17	65,5	15	10,5	10	18,7	8,5	8,5		
00743		Czerwony	35	(2)	10	3/8"	17	61	15	12	9,5	14	8,5	10,5		
00744		Czerwony	35	(2)	10	3/8"	17	69	15	12	9,5	18,7	8,5	10,5		
00749		Czerwony	35	(2)	12	1/2"	17	62	15	14	11,5	14	8,5	13		
00752		Czerwony	35	(2)	12	1/2"	17	70	15	14	11,5	18,7	8,5	13		
00831		Biały	50	(1/0)	6	#12	18,7	62,4	18	9	9	15,5	10	6,4	50/100	
00832		Czerwony	50	(1/0)	6	#12	18,7	69,7	18	9	9	20,8	10	6,4		
00837		Biały	50	(1/0)	8	5/16"	18,7	64,4	18	10	10	15,5	10	8,4		
00838		Czerwony	50	(1/0)	8	5/16"	18,7	71,7	18	10	10	20,8	10	8,4		
00843		Biały	50	(1/0)	10	3/8"	18,7	66,4	18	11	11	15,5	10	10,5		
00844		Czerwony	50	(1/0)	10	3/8"	18,7	73,7	18	11	11	20,8	10	10,5		
00849		Biały	50	(1/0)	12	1/2"	21	69,9	18	15,3	12	15,5	10	12,5		
00852		Czerwony	50	(1/0)	12	1/2"	21	77,2	18	15,3	12	20,8	10	12,5		
00855		Biały	50	(1/0)	14	9/16"	22	69,9	17	15,3	12	15,5	10	14,5	100/100	
00856		Czerwony	50	(1/0)	14	9/16"	22	77,2	17	15,3	12	20,8	10	14,5		
00937		Niebieski	70	(2/0)	8	5/16"	21,8	72,3	20,5	11	10	22	12	8,5		
00943		Niebieski	70	(2/0)	10	3/8"	21,8	78,3	20,5	14,5	11,2	22	12	10,5		
00949		Niebieski	70	(2/0)	12	1/2"	22	78,3	20,5	13	13	22	12	12,5		
00955		Niebieski	70	(2/0)	14	9/16"	22	78,3	20,5	14	11,3	22	12	14,5		
00961		Niebieski	70	(2/0)	16	5/8"	22	78,3	20,5	14	11,3	22	12	16,5		
05137		Biały	95	(3/0)	8	5/16"	25	76,8	23	12,5	12,5	26	13,8	8,5	50/50	
05143		Biały	95	(3/0)	10	3/8"	25	82,3	23	12,5	12,5	26	13,8	10,5		
05149		Biały	95	(3/0)	12	1/2"	25	84,3	23	14	13	26	13,8	12,5		
05155		Biały	95	(3/0)	14	9/16"	25	87,3	23	17	13	26	13,8	14,5		
05161		Biały	95	(3/0)	16	5/8"	25	87,3	23	17	13,5	26	13,8	16,5	25/25	
05237		Czerwony	120	(4/0)	8	5/16"	28	86	25	14	14	27	15,5	8,5		
05243		Czerwony	120	(4/0)	10	3/8"	28	86	25	14	14	27	15,5	10,5		
05249		Czerwony	120	(4/0)	12	1/2"	28	86	25	14	1					