BM GROUP	**Technical sheet**	**No.** 11TD01F **Issue** V02.1

Product family: Terminals - Uninsulated quick-connect terminals

Item code: 01198, 01199, 02198, 02199, 01298, 01299, 02298, 02299

Description: QUICK-CONNECT TERMINALS · UNINSULATED · PIGGY-BACKS

Image

Technical drawing



Specifications

TERMINAL MATERIAL: tinned/passivated brass
ACCORDING TO STD.: EN 61210: 2010-11
OPERATING TEMPERATURE: da -40 °C a +110 °C

Code	Material	Execution	Section (mm^2)	Section (AWG)	For male (mm)	For male (")	W1 (mm)	W2 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	
01198	passivated brass	loose	0.5 ÷ 1	(20 - 18)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	100/1000
01199	tinned brass	loose	0.5 ÷ 1	(20 - 18)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	
02198	passivated brass	reel	0.5 ÷ 1	(20 - 18)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	1300/1300
02199	tinned brass	reel	0.5 ÷ 1	(20 - 18)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	
01298	passivated brass	loose	1 ÷ 2.5	(18 - 14)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	100/1000
01299	tinned brass	loose	1 ÷ 2.5	(18 - 14)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	
02298	passivated brass	reel	1 ÷ 2.5	(18 - 14)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	1800/1800
02299	tinned brass	reel	1 ÷ 2.5	(18 - 14)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	1300/1300

CE