



Fisa tehnica

No.	12GA01A
Versiune	V02.0

Familie de produse:	Protecție pentru cabluri - Protecție termocontractabilă pentru cabluri
Cod produs:	GBS012BBI, GBS012BBL, GBS012BNE, GBS012BRO, GBS012BTR, GBS016BBI, GBS016BBL, GBS016BNE, GBS016BRO, GBS016BTR, GBS024BBI, GBS024BBL, GBS024BNE, GBS024BRO, GBS024BTR, GBS032BBI, GBS032BBL, GBS032BGV, GBS032BNE, GBS032BRO, GBS032BTR, GBS048BBI, GBS048BBL, GBS048BGV, GBS048BNE, GBS048BRO, GBS048BTR, GBS064BBI, GBS064BBL, GBS064BGV, GBS064BNE, GBS064BRO, GBS064BTR, GBS095BBI, GBS095BBL, GBS095BGV, GBS095BNE, GBS095BRO, GBS095BTR, GBS127BBI, GBS127BBL, GBS127BGV, GBS127BNE, GBS127BRO, GBS127BTR, GBS190BBI, GBS190BBL, GBS190BGV, GBS190BNE, GBS190BRO, GBS190BTR, GBS254BBI, GBS254BBL, GBS254BGV, GBS254BNE, GBS254BRO, GBS254BTR, GBS318BBI, GBS318BBL, GBS318BNE, GBS318BRO, GBS318BTR, GBS380BBI, GBS380BBL, GBS380BGV, GBS380BNE, GBS380BRO, GBS380BTR, GBS510BBI, GBS510BBL, GBS510BNE, GBS510BRO, GBS510BTR, GBS760BBI, GBS760BBL, GBS760BNE, GBS760BRO, GBS760BTR, GBS102BBI, GBS102BBL, GBS102BNE, PROTECȚIE CABLU · TERMOCONTRACTABILĂ · PERETE SUBȚIRE 2:1 · SUL
Descriere:	

Imagine	Desen tehnic

Specificații	
TIP:	perete simplu
RAPORT DE CONTRACȚIE:	2:1
MATERIAL:	polietilenă
TEMPERATURĂ DE OPERARE:	da -55°C a +125°C max (+105 °C max per trasparente)
TEMPERATURĂ DE CONTRACȚIE:	da +70°C a +125°C
TENSIUNE VRMS MAXIMĂ:	600 V
GRAD DE AUTO-STINGERE AL MANTALEI:	UL 224 VW-1 (eccetto trasparente e giallo-verde)
FĂRĂ HALOGENI:	toate culorile, cu excepția galben-verde și transparent
APLICAȚII:	izolație economică și eficientă și protecție pentru conexiuni și terminale în diverse industrii, inclusiv electronice, auto, feroviară și marină. Disponibilitatea mai multor culori face ușoară identificarea cablurilor.

Cod	Dimensiune tija (mm)	Lungime (m)		Culoare	D1 (Ø mm)	D2 (Ø mm)	S1 (mm)	 (m)
GBS012BBI*	1,2	200		Alb	1,2	0,6	0,38	200/200
GBS012BBL*	1,2	200		Albastru	1,2	0,6	0,38	
GBS012BNE*	1,2	200		Negru	1,2	0,6	0,38	
GBS012BRO*	1,2	200		Rosu	1,2	0,6	0,38	
GBS012BTR	1,2	200		Transparent	1,2	0,6	0,38	
GBS016BBI*	1,6	200		Alb	1,6	0,8	0,40	200/200
GBS016BBL*	1,6	200		Albastru	1,6	0,8	0,40	
GBS016BNE*	1,6	200		Negru	1,6	0,8	0,40	
GBS016BRO*	1,6	200		Rosu	1,6	0,8	0,40	
GBS016BTR	1,6	200		Transparent	1,6	0,8	0,40	
GBS024BBI*	2,4	200		Alb	2,4	1,2	0,48	200/200
GBS024BBL*	2,4	200		Albastru	2,4	1,2	0,48	
GBS024BNE*	2,4	200		Negru	2,4	1,2	0,48	
GBS024BRO*	2,4	200		Rosu	2,4	1,2	0,48	
GBS024BTR	2,4	200		Transparent	2,4	1,2	0,48	
GBS032BBI*	3,2	200		Alb	3,2	1,6	0,48	200/200
GBS032BBL*	3,2	200		Albastru	3,2	1,6	0,48	
GBS032BGV	3,2	200		GalbenVerde	3,2	1,6	0,48	
GBS032BNE*	3,2	200		Negru	3,2	1,6	0,48	
GBS032BRO*	3,2	200		Rosu	3,2	1,6	0,48	
GBS032BTR	3,2	200		Transparent	3,2	1,6	0,48	100/100
GBS048BBI*	4,8	100		Alb	4,8	2,4	0,48	
GBS048BBL*	4,8	100		Albastru	4,8	2,4	0,48	
GBS048BGV	4,8	100		GalbenVerde	4,8	2,4	0,48	
GBS048BNE*	4,8	100		Negru	4,8	2,4	0,48	
GBS048BRO*	4,8	100		Rosu	4,8	2,4	0,48	
GBS048BTR	4,8	100		Transparent	4,8	2,4	0,48	100/100
GBS064BBI*	6,4	100		Alb	6,4	3,2	0,56	
GBS064BBL*	6,4	100		Albastru	6,4	3,2	0,56	
GBS064BGV	6,4	100		GalbenVerde	6,4	3,2	0,56	
GBS064BNE*	6,4	100		Negru	6,4	3,2	0,56	
GBS064BRO*	6,4	100		Rosu	6,4	3,2	0,56	
GBS064BTR	6,4	100		Transparent	6,4	3,2	0,56	100/100
GBS095BBI*	9,5	100		Alb	9,5	4,8	0,62	
GBS095BBL*	9,5	100		Albastru	9,5	4,8	0,62	
GBS095BGV	9,5	100		GalbenVerde	9,5	4,8	0,62	
GBS095BNE*	9,5	100		Negru	9,5	4,8	0,62	
GBS095BRO*	9,5	100		Rosu	9,5	4,8	0,62	
GBS095BTR	9,5	100		Transparent	9,5	4,8	0,62	100/100
GBS127BBI*	12,7	100		Alb	12,7	6,4	0,62	
GBS127BBL*	12,7	100		Albastru	12,7	6,4	0,62	
GBS127BGV	12,7	100		GalbenVerde	12,7	6,4	0,62	
GBS127BNE*	12,7	100		Negru	12,7	6,4	0,62	
GBS127BRO*	12,7	100		Rosu	12,7	6,4	0,62	
GBS127BTR	12,7	100		Transparent	12,7	6,4	0,62	100/100
GBS190BBI*	19	100		Alb	19,1	9,5	0,89	
GBS190BBL*	19	100		Albastru	19,1	9,5	0,89	
GBS190BGV	19	100		GalbenVerde	19,1	9,5	0,89	
GBS190BNE*	19	100		Negru	19,1	9,5	0,89	
GBS190BRO*	19	100		Rosu	19,1	9,5	0,89	
GBS190BTR	19	100		Transparent	19,1	9,5	0,89	50/50
GBS254BBI*	25,4	50		Alb	25,4	12,7	0,89	
GBS254BBL*	25,4	50		Albastru	25,4	12,7	0,89	
GBS254BGV	25,4	50		GalbenVerde	25,4	12,7	0,89	
GBS254BNE*	25,4	50		Negru	25,4	12,7	0,89	
GBS254BRO*	25,4	50		Rosu	25,4	12,7	0,89	
GBS254BTR	25,4	50		Transparent	25,4	12,7	0,89	50/50
GBS318BBI*	31,8	50		Alb	31,8	15,9	1,00	
GBS318BBL*	31,8	50		Albastru	31,8	15,9	1,00	
GBS318BNE	31,8	50		Negru	31,8	15,9	1,00	
GBS318BRO*	31,8	50		Rosu	31,8	15,9	1,00	
GBS318BTR	31,8	50		Transparent	31,8	15,9	1,00	
GBS380BBI*	38	50		Alb	38,1	19,1	1,00	50/50
GBS380BBL*	38	50		Albastru	38,1	19,1	1,00	
GBS380BGV	38	50		GalbenVerde	38,1	19,1	1,00	
GBS380BNE*	38	50		Negru	38,1	19,1	1,00	
GBS380BRO*	38	50		Rosu	38,1	19,1	1,00	
GBS380BTR	38	50		Transparent	38,1	19,1	1,00	25/25
GBS510BBI	51	25		Alb	50,8	25,4	1,10	
GBS510BBL	51	25		Albastru	50,8	25,4	1,10	
GBS510BNE	51	25		Negru	50,8	25,4	1,10	
GBS510BRO	51	25		Rosu	50,8	25,4	1,10	
GBS510BTR	51	25		Transparent	50,8	25,4	1,10	
GBS760BBI	76	25		Alb	76,2	38,1	1,20	25/25
GBS760BBL	76	25		Albastru	76,2	38,1	1,20	
GBS760BNE	76	25		Negru	76,2	38,1	1,20	
GBS760BRO	76	25		Rosu	76,2	38,1	1,20	
GBS760BTR	76	25		Transparent	76,2	38,1	1,20	
GBS102BBI	102	25		Alb	101,6	50,8	1,35	25/25
GBS102BBL	102	25		Albastru	101,6	50,8	1,35	
GBS102BNE	102	25		Negru	101,6	50,8	1,35	
GBS102BRO	102	25		Rosu	101,6	50,8	1,35	
GBS102BTR	102	25		Transparent	101,6	50,8	1,35	