

**Product family:** Products no longer in pricelist - Hydraulic equipment  
**Item code:** 283  
**Description:** [OLD] CRIMPING HEAD - FOR PUMPS - UP TO 240 mm<sup>2</sup> (SERIES 83)

**Image**



**Features**

Replaced by  
 • 283 --> 2833

**FEATURES:**

- pivot opening
- with male quick coupling fitting with automatic locking
- for operation it must be combined with a pump with an operating pressure of 700 bar

**Specifications**

**CRIMPING FORCE AT DIE LEVEL:**

80 kN

**DIES:**

83 series

**FIELD OF USE:**

terminals

- uninsulated and DIN from 10 to 240 mm<sup>2</sup> (180 mm<sup>2</sup> for DIN)
- uninsulated class 6 from 10 to 185 mm<sup>2</sup>
- medium voltage from 25 to 240 mm<sup>2</sup>
- aluminum from 16 to 185 mm<sup>2</sup>
- bimetallic from 16 to 150 mm<sup>2</sup>
- bimetallic DIN from 16 to 185 mm<sup>2</sup>
- insulated from 10 to 95 mm<sup>2</sup>
- C shunt from 10 to 95 mm<sup>2</sup>
- end-sleeve from 50 to 150 mm<sup>2</sup>

Code	Description	Length (mm)	Width (mm)	Thickness (mm)	Weight (kg)	Pack size LxWxH (mm)	
283	80 kN crimping head for pump	290	70	70	3,3	350x250x100	VA

**SERIE83**