

Product family: Hydraulic equipment - Pumps and headstocks
Item code: 284, 284L
Description: CRIMPING HEADSTOCK · FOR PUMPS · UP TO 400 mm² (SERIES 84)

Image



Features

- “C” opening for easy joint crimping (the maximum conductor section depends on cable insulation thickness)
- bigger “C” opening in 284L version to crimp big section joints
- with male quick coupling fitting with automatic locking
- for operation it must be combined a pump with an operating pressure of 700 bar

Specifications

CRIMPING FORCE AT DIE LEVEL: 120 kN
DIES: 84 series
FIELD OF USE: terminals

- uninsulated from 10 to 400 mm² (300 mm² for DIN)
- uninsulated class 6 from 10 to 185 mm²
- medium voltage from 25 to 400 mm²
- aluminum from 16 to 240 mm²
- bimetallic from 16 to 300 mm²
- bimetallic DIN from 16 to 300 mm²
- insulated from 10 to 240 mm²
- C shunt from 10 to 150 mm²
- end-sleeve from 50 to 150 mm²

Code	Description	Max “C” opening (mm)	Length (mm)	Width (mm)	Thickness (mm)	Weight (kg)	Pack size LxWxH (mm)	
284	120 kN crimping headstock for pump	30	245	115	68	4	440x270x130	VA
284L	120 kN crimping headstock for pump	42	250	130	70	5,3	440x270x130	

SERIE84