BM GROUP	**Technical sheet**	**No.** 41MD02B **Issue** V01.1

Product family: Terminal blocks - Automatic crimping connectors

Item code: 01031, 01032, 01033, 01033R, 01034, 01036, 01039

Description: ACCESSORIES FOR CRIMPING CONNECTORS · M620 SERIES · MALE HOUSING

Image

Specifications

INSULATING HOUSING IN: polyamide (PA 6.6) natural color

DIELECTRIC STRENGTH: 1500 AC-1 minute V

INSULATION SELF-EXTINGUISHING: UL 94 V2

Code	Type	Operating temperature	Shells Material	Shells Color	Ways	Rated voltage (V)	Current (A)	
01031	male	from -25 °C to 105 °C max	PA 6.6	Natural	1	300	15	1000/1000
01032	male	from -25 °C to 105 °C max	PA 6.6	Natural	2	300	15	500/500
01033	male	from -25 °C to 105 °C max	PA 6.6	Natural	3	300	14	
01033R	male	from -25 °C to 105 °C max	PA 6.6	Red	3	300	14	
01034	male	from -25 °C to 105 °C max	PA 6.6	Natural	4	300	13	
01036	male	from -25 °C to 105 °C max	PA 6.6	Natural	6	300	12	300/300
01039	male	from -25 °C to 105 °C max	PA 6.6	Natural	9	300	9	200/200