BM GROUP	**Technical sheet**	**No.** 75RD01A **Issue** V01.0

Product family: Conduit fixings - Accessories for spiral conduits

Item code: TP5RGM10, TP5RGMN10, TP5RGM12, TP5RGMN12, TP5RGM16, TP5RGMN16, TP5RGM20, TP5RGMN20, TP5RGM25, TP5RGMN25, TP5RGM32, TP5RGMN32, TP5RGM40, TP5RGMN40, TP5RGM50, TP5RGMN50

Description: IP65 ACCESSORIES FOR SPIRAL CONDUITS · SWIVEL FITTING · METRIC THREAD · RGM/RGMN

Image

Specifications

MATERIAL:	fireproof polypropylene
PITCH:	metric
RESISTANCE TO SHOCK:	class 3 (>2 kg from 10 cm at -5 °C)
MIN. TEMPERATURE:	class 2 (-5 °C)
MAX. TEMPERATURE:	class 1 (+60°C)
RESISTANCE TO FIRE:	self-extinguishing
GLOW WIRE TEST:	pass at 850 °C
PROTECTION GRADE:	IP65
STANDARD:	EN 61386-1, EN 61386-23

Code	Color	Metric thread (EN 60423)	Sheathing diameter (mm)	
TP5RGM10	6971	M 12 x 1.5	10	10/150
TP5RGMN10	6972	M 12 x 1.5	10	
TP5RGM12	6971	M 16 x 1.5	12	10/150
TP5RGMN12	6972	M 16 x 1.5	12	
TP5RGM16	6971	M 20 x 1.5	16	10/100
TP5RGMN16	6972	M 20 x 1.5	16	
TP5RGM20	6971	M 25 x 1.5	20	10/70
TP5RGMN20	6972	M 25 x 1.5	20	
TP5RGM25	6971	M 32 x 1.5	25	10/40
TP5RGMN25	6972	M 32 x 1.5	25	
TP5RGM32	6971	M 40 x 1.5	32	5/25
TP5RGMN32	6972	M 40 x 1.5	32	
TP5RGM40	6971	M 50 x 1.5	40	5/20
TP5RGMN40	6972	M 50 x 1.5	40	
TP5RGM50	6971	M 63 x 1.5	50	5/15
TP5RGMN50	6972	M 63 x 1.5	50	

CE

IP65